



AFP7Y64T | FP7 Input and Output units



※Photo may vary from actual product.

Product Number	AFP7Y64T
Part Number	AFP7Y64T
Product	FP7 Input and Output Units
Details	Output units
Product name	FP7 Input and Output units

Spec Detail

As of May 30, 2021

Specifications and design of the products are subject to change without notice for the product improvement.

Item		Specifications
Product Number	AFP7Y64T	
Part Number	AFP7Y64T	
[[OUTPUT SPECIFICATIONS]]Insulation method		Photocoupler insulation
[[OUTPUT SPECIFICATIONS]]Rated control capacity		-
[[OUTPUT SPECIFICATIONS]]Min. load		-
[[OUTPUT SPECIFICATIONS]]Output type		Open collector
[[OUTPUT SPECIFICATIONS]]Rated load voltage		5 to 24 V DC
[[OUTPUT SPECIFICATIONS]]Load voltage allowable range		4.75 to 26.4 V DC
[[OUTPUT SPECIFICATIONS]]Max. load current:0.3 A (Y0 to Y7)		0.3 A (20.4 to 26.4 V DC), 30 mA (4.75 V DC)
[[OUTPUT SPECIFICATIONS]]Max. load current:0.1 A (other than that above)		0.1 A (20.4 to 26.4 V DC), 15 mA (4.75 V DC)
[[OUTPUT SPECIFICATIONS]]Common restriction		3.2 A/common
[[OUTPUT SPECIFICATIONS]]Max. surge current		0.6 A
[[OUTPUT SPECIFICATIONS]]OFF state leakage current		1 micro A or less
[[OUTPUT SPECIFICATIONS]]ON state maximum voltage drop		0.5 V or less
[[OUTPUT SPECIFICATIONS]]Repose time:OFF→ON		0.1 ms or less (at load current 2 mA or more)
[[OUTPUT SPECIFICATIONS]]Repose time:ON→OFF		0.3 ms or less (at load current 1 mA or more)
[[OUTPUT SPECIFICATIONS]]Life time:Mechanical life		-
[[OUTPUT SPECIFICATIONS]]Life time:Electrical life		-

[[OUTPUT SPECIFICATIONS]]External power supply:Voltage	4.75 to 26.4 V DC
[[OUTPUT SPECIFICATIONS]]External power supply:Current (at 24 V)	70 mA/common
[[OUTPUT SPECIFICATIONS]]Surge absorber	Zener diode
[[OUTPUT SPECIFICATIONS]]Relay socket	-
[[OUTPUT SPECIFICATIONS]]Short circuit protection	-
[[OUTPUT SPECIFICATIONS]]Output points per common	32 points/common
[[OUTPUT SPECIFICATIONS]]Operating mode indicator	32 points LED display (lights when ON, selectable by switch)
[[OUTPUT SPECIFICATIONS]]External connection method	Connector (MIL-compliant 40 pins, two use)
[[COMMON GENERAL SPECIFICATIONS]]Ambient temperature	0 to +55 °C +32 to +131 °F, Storage: -40 to +70 °C -40 to +158 °F
[[COMMON GENERAL SPECIFICATIONS]]Ambient humidity	10 to 95 % RH (at +25 °C +77 °F, no condensation), Storage: 10 to 95 % RH (at +25 °C +77 °F, no condensation)
[[COMMON GENERAL SPECIFICATIONS]]Breakdown voltage	500 V AC for 1 minute (Note) The breakdown voltage is 2,300 V AC, 1 minute.
[[COMMON GENERAL SPECIFICATIONS]]Insulation resistance	100 MOhm or more (at 500 V DC)
[[COMMON GENERAL SPECIFICATIONS]]Vibration resistance	5 to 8.4 Hz, single amplitude of 3.5 mm 0.138 in, 1 sweep/min. (IEC 61131-2) ; 8.4 to 150 Hz, constant acceleration of 9.8 m/s ² , 1 sweep/min. (IEC 61131-2), 10 times each in X, Y, and Z directions
[[COMMON GENERAL SPECIFICATIONS]]Shock resistance	147 m/s ² or more , 3 times each in X, Y, and Z directions (IEC61131-2)
[[COMMON GENERAL SPECIFICATIONS]]Noise immunity	1,000 V [p-p] with pulse width 50 ns and 1 micro s (using a noise simulator)
[[COMMON GENERAL SPECIFICATIONS]]Operating condition	Free from corrosive gasses and excessive dust
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Rated voltage range	-
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Current consumption	75 mA or less
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Net weight	115 g approx.

Accessories

		
Product Number AFP2801	Product Number AFP2802	Product Number AXW7221FP
Part Number AFP2801	Part Number AFP2802	Part Number AXW7221FP
Product name Discrete-wire connector set	Product name Flat cable connector set	Product Pressure contact for multi-wire
		Product name Pressure contact for multi-wire



Product Number **AXW7231FP**

Part Number **AXW7231FP**

Product **Pressure contact for multi-wire**

Product name **Pressure contact for multi-wire**

Product Number **AXY52000FP**

Part Number **AXY52000FP**

Product **Pressure contact tool**

Details **Multi-wire connector pressure contact tool**

Product name **Pressure contact tool**